Section 1 - Identification

Product Identifier: TSR-2 Racing Oil 50

Supplier Phone:727-733-2054Supplier:Lightning Connecting Rods

Emergency Phone & Hours: 727-733-2054 Hrs: 24 Hrs. 7 days

Supplier Address: 1630 N. HERCULES AVE. STE-B

CLEARWATER, FL 33765

Intended Use Lubrication of Tools

Uses To Avoid Non-intended use

Section 2 - Hazard Identification

Signal Word: DANGER

Other than flammability, no specific data exists for this mixture. Hazard classifications are calculated

based on component information.

Hazard Classifications: Substance Or Mixture Mixture

Acute Toxicity Dermal (Category 5), Acute Toxicity Inhalation (Category 4), Eye damage/irritation (Category 2B), Respiratory Sensitizer (Category 1B), Skin Sensitizer (Category 1B), Aquatic Hazard-short term (Category 2), Aquatic Hazard-long term (Category 2), Skin Corrosion/Irritation (Category 3),

Hazard Statements based on component information:

HAZARDS: May be harmful in contact with skin. Harmful if inhaled. Eye contact causes mild eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Skin contact causes mild skin irritation.

Precautions:

Before handling, put on eye protection, chemical resistant gloves, and cover all exposed skin. Use only with good ventilation or wear NIOSH approved organics respirator.

Pictograms:

(Area to right is blank if no pictograms apply)





Other Hazards Not Resulting In Classification: May be hazardous to soil dwelling organisms.

Summary: Read entire SDS prior to use. Observe all precautions. Use engineering controls to minimize human exposure to workplace chemicals.

	_	
Section 3 - Composition	/ Information	on Ingredients

Component	CAS Number	% Range	
PETROLEUM HYDROCARBON	MIXTURE	40 - 60	Exact percentages and component identities are being witheld as trade secrets. Occupational Exposure Levels, Toxicity, and Ecological information on components is shown in Sections 8, 11, and 12 below. Users should read and understand the entire SDS. More specific information on components will be released to medical professionals in case
MINERAL OIL	MIXTURE	5 - 15	
PARAFFINIC DISTILLATE	MIXTURE	15 - 40	
RUST INHIBITOR	MIXTURE	1 - 5	
LUBRICANT ADDITIVE MIXTURE	MIXTURE	1 - 5	
LUBRICANT ADDITIVE MIXTURE	MIXTURE	5 - 15	of emergency.
TRADE SECRET COMPONENT	PROPRIETARY	5 - 15	

Section 4 - First Aid Measures:

TSR-2 Racing Oil 50

Page 2

First responders should wear clothing appropriate for industrial exposure in accordance with local codes. At a minimum, all exposed skin should be covered, and latex gloves and eye protection meeting ANSI Z87 or CSA Z94.3 should be worn. First responders should avoid contact with spilled material. Spills of this material present a slip hazard. If smoke, fumes, or airborne mist is present, first responders should use organics respirator or self contained breathing apparatus.

IF SWALLOWED: Get immediate medical attention. Call poison control center.

IF IHHALED: Remove affected person to fresh air and make comfortable for breathing. Get immediate medical attention.

IF IN EYES: Rinse eyes with water. Get immediate medical attention if irritation persists.

IF ON SKIN: Wash skin with cool water. Get medical attention if irritation persists.

IF ON CLOTHES: Do not allow skin contact with contaminated clothing. Remove contaminated clothing and wash before re-use.

IF EXPOSED: Contact physician if you feel unwell.

Most Important Symptoms ACUTE: Respiratory effects, vision effects.

DELAYED: Dermatological effects.

Indication of Immediate Medical Attention Difficulty breathing, dizziness, extreme drowsiness, eye irritation, loss of vision, skin rash.

Section 5 - Fire Fighting Measures:

Appropriate Extinguishing Media Avoid spraying water jet on burning liquids as this may spread the fire. Use dry chemical or foam extinguishing media.

Specific Fire Hazards

Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

Keep containers cool with water spray. Evacuate local area until fire is controlled.

Special Protective Actions

Section 6- Accidental Release Measures:

Personal Precautions

Spills present a slip hazard. Extinguish/disconnect possible sources of ignition near spill. Ensure adequate ventilation of fumes from affected area. Remove unneccesary personnel from area around spill. Prior to cleaning up, don protective gear including chemical and hydrocarbon resistant outer layer, latex or rubber gloves, rubber boots, and eye protection. Emergency responders should wear chemical and hydrocarbon resistant gear.

Environmental Precautions

Small spills may be wiped up with rags. For spills >10 litres- if possible to safely do so, contain the spilled material using diatomaceous earth and/or absorbent pads. Dike drains and prevent material from entering sewers, ditches, drains, or water courses. Place absorbed material into sealed storage containers and consult an environmental expert for proper disposal measures. Immediately report any discharges that escape containment to the local environmental authority or fire department.

Methods for Cleaning Up

Absorption with diatomaceous earth and/or absorbent pads is best. Do not use vacuum. Do not wash hydrocarbon or chemical spills away into sewers or drains. Use proper disposal methods for spent absorbents and contaminated rags or clothing.

Section 7- Storage and Handling:

TSR-2 Racing Oil 50

Page 3

Precautions for Handling

Wear protective gear including skin, hand, and eye protection when handling this material. Use with good ventilation or wear NIOSH approved respirator with organic vapor cartridges. Transfer large amounts using pumps and lines that are properly maintained. Visually inspect hoses and replace worn or suspicious looking hose and/or fittings. Use clean containers with sealing lids to transfer small amounts. Use caution when pouring to avoid splashing into eyes or on skin. Do not handle open containers near flames or hot surfaces.

Methods for Safe Storage

Store containers indoors away from heat and flames. Store in secure location with good ventilation. Keep container sealed when not transferring product. Protect from rain and extreme cold.

Avoid storage of hydrocarbons near strong mineral acids or materials marked 'Oxidizer'.

Section 8- Exposure Controls/Personal Protection:

Control Parameters

No exposure limits are established for this mixture. Information on individual components is provided below.

Component Information - Occupational Exposure Limits:

PETROLEUM HYDROCARBON US ACGIH: TWA: 5 mg/m3, STEL: 10 mg/m3 (as Oil Mist, if generated); US OSHA: 5 mg/m3 TWA as Oil Mist, if generated

MINERAL OIL None Established

PARAFFINIC DISTILLATE US ACGIH: TWA: 5 mg/m3, STEL: 10 mg/m3 (form: Inhalable fraction); US OSHA: 5 mg/m3 TWA (form: Inhalable fraction)

RUST INHIBITOR None Established

LUBRICANT ADDITIVE MIXTURE 5mg/m3

LUBRICANT ADDITIVE MIXTURE None Established
TRADE SECRET COMPONENT None Established

Personal Protective Gear

Workers exposed to airborne levels above threshold values shown above should use protective gear including safety glasses, latex gloves, long sleeve work shirts, long pants, hair covering, and work shoes having oil and chemical resistant soles. Similar protective gear should be worn when servicing equipment containing this material, or when draining and refilling equipment with fresh product.

Engineering Controls

Engineering controls should ensure adequate ventilation to keep airborne concentrations below threshold values shown above. Pumps and handling equipment should be designed to reduce human exposure potentials to liquids being transferred from containers into closed systems.

Section 9- Physical Properties:

TSR-2 Racing Oil 50

Page 4

Appearance Clear Liquid **Upper Explosive Limit** Unknown Odor Characteristic **Lower Explosive Limit** Unknown **Odor Threshold** Unknown Vapour Pressure <1 mm Hg pН NA- anhydrous **Vapour Density** >1 (air = 1)

Not applicable **Melting Point Relative Density** .82 - .92 kg/l @ 25C

Freezing Point <0 C Solubility Hydrocarbons, insoluble in water

Initial Boiling Point >100 C **Partition Coefficient** Unknown **Boiling Range** Unknown **Auto Ignition Temp** Unknown **Flash Point** >93C **Decomposition Temp** Unknown

Evaporation Rate <1 (n-butyl acetate=1) Viscosity cSt 40C

Section 10- Physical Properties:

Reactivity May react violently if combined with strong oxidizers and heat.

Chemical Stability Stable under recommended storage conditions.

Conditions to Avoid Keep away from fire, sparks, and other sources of ignition.

Possibly Hazardous Reactions None known.

> **Incompatible Materials** Strong acids and materials marked 'Oxidizer'.

Hazardous Decomposition Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of

Products nitrogen, and heavy, acrid smoke.

Section 11- Toxicological Information:

Likely Routes of Exposure Dermal and eye exposure from normal use conditions. Ingestion and inhalation are not likely if all

precautions for use are followed. **Symptoms of Exposure:**

> Ingestion minimal amounts, e.g. failure to wash hands before eating/smoking, is unlikely to cause Ingestion

symptoms. Swallowing of liquid product may cause vomiting and nausea.

Inhalation results in coughing and may cause difficulty breathing. Inhalation

Transient dermal contact is not irritating. Prolonged dermal contact may cause local irritation and Dermal/Eye

rash. Eye contact causes mild to severe eye irritation and possible temporary loss of vision.

Immediate or Delayed Effects No data available

Interactive Effects No data available

Numerical Measures of Toxicity - components

PETROLEUM HYDROCARBON: LD50 5001 mg/Kg; MINERAL OIL: Non Hazardous; PARAFFINIC DISTILLATE: Non Hazardous; RUST INHIBITOR: Non Hazardous; LUBRICANT ADDITIVE MIXTURE: Non Hazardous **Acute Oral**

Toxicity:

PETROLEUM HYDROCARBON: LD50 5001 mg/kg; MINERAL OIL: Non Hazardous; PARAFFINIC DISTILLATE: LD50 2001-5000mg/kg; RUST INHIBITOR: LD50 2001-5000mg/kg; LÜBRICANT ADDITIVE MIXTURE: Non Hazardous **Acute Skin** Toxicity:

Section 11- Toxicological Information: (continued)

TSR-2 Racing Oil 50

Page 5

Acute Toxicity Inhalation

PETROLEUM HYDROCARBON: Non Hazardous; MINERAL OIL: Non Hazardous; PARAFFINIC DISTILLATE: Non Hazardous; RUST INHIBITOR: LD50 10=20mg/l; LUBRICANT ADDITIVE MIXTURE: Non Hazardous

Skin Corrosion: PETROLEUM HYDROCARBON: Cat 3 Irritant; MINERAL OIL: Non Irritating; PARAFFINIC DISTILLATE: Cat 3 Irritant; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: Non Irritating

PETROLEUM HYDROCARBON: Cat 2B Eye Irritant; MINERAL OIL: Non-Categorized, Suspected Eye Irritant; PARAFFINIC DISTILLATE: Non-Categorized, Suspected Eye Irritant; RUST INHIBITOR: Non-Categorized, Suspected Eye Irritant; LUBRICANT ADDITIVE MIXTURE: Cat 2A Serious Irritation

Respiratory Sensitizatión: PETROLEUM HYDROCARBON: Non Sensitizing; MINERAL OIL: Non Sensitizing; PARAFFINIC DISTILLATE: Cat 1B Sensitizer; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: Non Sensitizing

Skin Sensitization: PETROLEUM HYDROCARBON: ; MINERAL OIL: Non Sensitizing; PARAFFINIC DISTILLATE: Cat 1B Sensitizer; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: Non Sensitizing

Germ Cell Mutagenicity: PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: No Data Available; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available

Carcinogen:

PETROLEUM HYDROCARBON: No Hazard; MINERAL OIL: No Hazard; PARAFFINIC DISTILLATE: No Hazard; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Hazard

Section 11- Toxicological Information: (continued)

TSR-2 Racing Oil 50

PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: No Data Available; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available Reproductive Effects:

Page 6

Target Organ 1 Exposure:

PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: No Data Available; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available

Target Organ Multiple **Exposure:**

PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: No Data Available; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available

Aspiration Hazard:

PETROLEUM HYDROCARBON: No Hazard; MINERAL OIL: No Hazard; PARAFFINIC DISTILLATE: No Hazard; RUST INHIBITOR: No Hazard; LUBRICANT ADDITIVE MIXTURE: No Hazard

Other Information No other information available.

Section 12- Ecological Information:

Ecological Summary Hydrocarbon mineral oils have low toxicity and are inherently biodegradable. Additives in mixture have

varying degrees of toxicity, persistance, and other effects. Available component data is shown below.

Bioaccumulation No data available

Persistance/Degradability No data available

Waste Treatment Effects No data available.

Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low. Soil Mobility

Oils spilled or leaked into waterways will cause an oil sheen on the surface. **Other Adverse Effects**

Toxicity to aquatic organisms, component information:

PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: Non Toxic; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available Aquatic Toxicity,

Acute:

Section 12- Ecological Information, Continued:

TSR-2 Racing Oil 50

Page 7

Aquatic Toxicity,Long Term: PETROLEUM HYDROCARBON: No Data Available; MINERAL OIL: No Chronic Aquatic Toxicity; PARAFFINIC DISTILLATE: No Data Available; RUST INHIBITOR: No Data Available; LUBRICANT ADDITIVE MIXTURE: No Data Available

Ozone: No components of this mixture are known to cause any adverse effects on the earth's ozone layer.

Section 13- Disposal Considerations:

Disposal Containers & Methods Unused material is not a RCRA hazardous waste. Mixture with other wastes may cause

classification as hazardous waste. Users must determine compliance with local, state, and federal

regulations for proper classification and disposal of used oils.

Physical Chemical Properties

Affecting Disposal

Changes in physical and chemical properties during use, such as contamination with heavy metals,

may affect classification for disposal. Test prior to disposal.

Improper Disposal Discharging of oily wastes into any sewer, watercourse, or unregulated drain is improper and may

result in fines, penalties, cleanup costs, and criminal liabilitites.

Precautions for Landfill Oily liquid should not be disposed in a landfill. Disposal of oily absorbents, rags, or other items into

a landfill should only be done with proper permission from local, state, and federal authorities.

Section 14- Transport Information:

US DOT 49 CFR Parts 171-180:

Proper Shipping Name Not Regulated for Domestic Shipment UN/ID/NA Number:

Transport Hazard Class NA Packing Group NA Labels: NA ERGCode NA

Marine Pollutant: No

IATA-DGR

IATA Proper Shipping Name Not Regulated UN/ID Number

IATA Class IATA Packing Group: IATA Labels

IMDG-CODE

IMDG Proper Shipping Name Not Regulated

IMDG UN/ID Number IMDG Shipping Class IMDG Packing Group

IMDG Labels IMDG Marine Pollutant: No

MARPOL 73/78 Annex II

MARPOL Not available for sale in bulk marine shipments

Special Precautions None

Section 15- Regulatory Information:

TSR-2 Racing Oil 50

Page 8

TSCA Inventory: All components properly registered.

US SARA 313 No components are subject to the reporting requirements.

SARA 311/312 Acute Health Hazard None SARA 311/312 Chronic Health Hazard None

SARA 311/312 Fire Hazard None SARA 311/312 Sudden Release of Pressure None

SARA 311/312 Reactivity Hazard No hazard

California Proposition 65 This material does not contain any chemicals which are known to the State of California to

cause cancer, birth defects or other reproductive harm at concentrations that trigger the

warning requirements of California Proposition 65.

Other Regulations

REACH All components are listed on REACH registry.

Canada WHMIS - No hazard class

Section 16- Other Information:

Revision Date May 28, 2015

Reasons For Revision Initial GHS SDS preparation.

Sec 16 Other Info

This Safety Data Sheet was prepared in good faith from the most recent information available, in accordance with current GHS regulations in effect at time of preparation. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.